

CISCO 300-625

QUESTIONS AND ANSWERS

FREE VERSION

(LIMITED CONTENT)

Thank you for downloading our reliable exam questions for more exams you can visit:

https://www.pass4it.com/all-vendors

Dumps Questions 300-625
Exam Name:
Certification Provider: Cisco
Exam: Configuring Cisco MDS 9000 Series Switches (DCSAN)
Question #1
Which two steps are mutual between Cisco secure boot and UEFI secure boot? (Choose two.)
A. bootloader
B. operating system
C. microloader
D. kemel
E. hardware anchor
Correct Answer: AB
0
Question #2
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits.
Which feature on MDS platforms ensures that the code that is running on the hardware platform is
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits.
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot B. UEFI Secure Boot
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot B. UEFI Secure Boot C. Secure Unique Device Identifier
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot B. UEFI Secure Boot C. Secure Unique Device Identifier D. BIOS Secure Boot Correct Answer: A
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot B. UEFI Secure Boot C. Secure Unique Device Identifier D. BIOS Secure Boot Correct Answer: A Question #3
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot B. UEFI Secure Boot C. Secure Unique Device Identifier D. BIOS Secure Boot Correct Answer: A Question #3 Which component is initially responsible for loading the kickstart image on Cisco MDS Switches?
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot B. UEFI Secure Boot C. Secure Unique Device Identifier D. BIOS Secure Boot Correct Answer: A Question #3 Which component is initially responsible for loading the kickstart image on Cisco MDS Switches? A. ROMMON
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot B. UEFI Secure Boot C. Secure Unique Device Identifier D. BIOS Secure Boot Correct Answer: A Question #3 Which component is initially responsible for loading the kickstart image on Cisco MDS Switches? A. ROMMON B. BIOS
Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits. A. Cisco Secure Boot B. UEFI Secure Boot C. Secure Unique Device Identifier D. BIOS Secure Boot Correct Answer: A Question #3 Which component is initially responsible for loading the kickstart image on Cisco MDS Switches? A. ROMMON

Correct Answer: C

Question #4

A network engineer must run a core Cisco Nexus 9500 Series Switch as a POAP server for all top-of-rack Cisco Nexus switches. Which two network functions must run to provide the POAP service? (Choose two.)

- A. DNS
- B. PXE
- C. BOOTP
- D. TFTP
- E. DHCP

Correct Answer: DE